



### Connector US-Cross II



#### Application

Cross connection  
For Ball & Socket Z sheet piles only

#### Advantages

Equal spacing system ensures easy planning and safe installation without the need for cutting, bending or other fabrication piles and eliminates most welding.

#### Properties

Steel grades:	S355, S572 Grade 50
Steel thickness:	8 mm 0.32"
Lengths:	on request, from 7.6 m - 10.6 m 25 to 35 ft, hot extruded
Weight:	20 kg/m 13.4 lbs/ft

Seamless cross sections, made from one piece of steel.  
Minimum angle flexibility of at least 30° each interlock.  
Provide maximum safety margin by the primary load absorption properties of the connecting webs within the clutches.  
All connectors are compatible with each other.  
Also available as 100% melted and manufactured in the USA.

Connectors are **not suitable for single driving**. Please insert the connector before driving into the sheet pile interlock, tack it with welds and drive it together with the sheet pile (EN12063).

SteelWall connectors generally comply with the European standards and are manufactured by certified steel processing companies. All figures are approximate and may vary. Bar twists are possible up to 0.025" per foot (2 mm per meter). Tolerance of steel thickness  $\pm 0.04"$  ( $\pm 1$  mm). Length tolerance up to  $\pm 7.9"$  ( $\pm 200$  mm). Degree details refer to the connector bar axes. We reserve the right to make technical changes. We refer to DIN EN 12063. Please check the sheet pile interlocks with a physical sample section of the desired connector for compatibility.

SteelWall ISH GmbH  
Tassilostr. 21  
82166 Gräfelfing  
Germany  
E-mail: info@steelwall.eu

SteelWall US, Humphrey Chang  
US sales line 8:30 am to 4:30 pm (Arizona time)  
Toll free 1(888) 309 2250  
Fax: 1(888) 743 7712  
E-mail: chang@steelwallus.com

Australia  
Caribbean  
New Zealand  
North America  
South East Asia

Copyright by  
SteelWall ISH GmbH  
2022-May-10

[steelwallus.com](http://steelwallus.com)